



oxyturbo®

Gas in Action

WELDING KITS & GARDEN



SMALL WELDING KITS, SMALL WELDERS
MONOGAS WELDING AND OUTDOOR MAINTENANCE
PRODUCTS FOR HOMES AND GARDENS.

AUTHORITY RECOGNISED BY THE MARKET



The Oxyturbo identity is as a partner as well as an effective supplier

Oxyturbo is present in the market as a proactive, safe reference for a wide range of products and a vast span of application fields. In each of these, the company has asserted its identity as a customer partner, based on three key concepts: the search for innovative solutions, product quality assurance, and versatility of response to market demands. The company's established experience, gained with the manufacturing and marketing of hundreds of products, focuses on constant collaboration with its partners, both in Italy and on the worldwide stage. These same partners can attest to the authoritativeness of their "company system".

RESEARCH AND DEVELOP INNOVATION

Exceeding your own limits: the most exciting challenge

Since its inception, Oxyturbo has always aimed to diversify and broaden its offer, both by looking at internationally applied research developments and by developing a strong internal R&D commitment. Oxyturbo research efforts have consistently aimed at introducing increasingly high performing, durable, eco-friendly, innovative systems. The Oxyturbo research team is one of the most prominent facilities in the industry thanks to their functionality, ease of use and safety of the products it has developed.



"TAILOR MADE" SOLUTIONS

Facilitating technical and commercial decisions for customers

Understanding customer needs and making products that meet these requirements have always been the core values behind the relationship between Oxyturbo and the market. Customers find a trusted reference in Oxyturbo, a real "facilitator" of technical and commercial decisions, able to identify and create the solutions that are needed and to contribute to the creation of value. The company also knows how to give the most targeted answers to each specific need, supporting them with an integrated service organisation that plans and delivers an equally versatile supply of products.

PRODUCTION WITH "SMART MANUFACTURING" LOGIC

Avant-garde facilities and 4.0 chain organisation

The Oxyturbo facilities which includes machines and robotic and digital systems have long been the main players in all their main manufacturing phases, even before the concept of Factory 4.0 was affirmed as a must in intelligent industry. Oxyturbo was one step ahead of those developments that today are strategic for modern manufacturing, ensuring production process efficiency, controlling the entire supply chain and safeguarding stringent qualitative parameters. It also ensures the accuracy of finishes and treatments of both metals and other elements and constructive details.



CERTIFIED, SELECTED QUALITY

The certainty of original Oxyturbo reliability



The Oxyturbo quality system is certified to EN ISO 9001. A traceability system is also used to follow the life of each product with a specific "manufacturing memory". The company has also created a special "brand" of origin that guarantees authenticity as "original Oxyturbo". As part of this logic of customer respect, the company focuses on the safety and reliability of products with a very competitive cost range. Selected products from the world market are directly tested for consistency with the company commitment to quality.



ICT LOGISTICS SYSTEM

Digital platforms for combined speed, diversification and precision

Quickness, availability and flexibility are all key components of the Oxyturbo logistics organisation. A proven, modern system with the latest Information Communication Technology, allowing orders to be executed in a fast and accurate manner. This is also bolstered by a dynamic response to constant stock availability of products, which are also equipped with their packaging. The system is controlled with digital platforms and process sensors within the company's commitment to a concrete "environment 4.0".





PRODUCT INDEX

SMALL WELDING KITS

TURBO SET 200	6
TURBO SET 110	7
TURBO SET 90	8
TURBO SET 30	9
SPARE PARTS AND ACCESSORIES	10
FILLER METALS	11

SMALL WELDERS

OXYLASER	13
OXYFLEX	14
MAXYLASER AND MINILASER	15
MANUAL TORCHES	16
HEATING TORCH KITS	17
DISPOSABLE CYLINDERS AND CARTRIDGES	18
GAS CONTROL	19

MONOGAS WELDING

WITH RECHARGEABLE CYLINDERS

OXYWELDING	21
ACCESSORIES	23
OXYWELDER KITS	24

GARDEN

BIOFLAMME	28
SUPEBIOFLAMME	29
BIOMEGAFLAMME	30
LASERBRENNER	31
BIOPROFLAMME	32
BIOSUPERPROFLAMME	33
CYLINDER HOLDER TROLLEYS	34
SPARE PARTS AND ACCESSORIES	35

The data and images contained in this catalogue are purely indicative and may be subject to change without notice by Oxyturbo SpA. Photographs and descriptions of products do not have any contractual value.

EN ISO 1326

TURBO SET SMALL WELDING KITS

**Small kits with great success for gas welding
with disposable cylinders and cartridges.
Practical and easy to handle, offering excellent results
in multiple uses.**

The international standard of comparison for those offering autogenous welding sets with non-refillable oxygen cylinders and gas cartridges. All contained in an elegant, small size metal trolley that allows for easy and convenient transportation thanks to its cylinder locking devices.

Turbo Sets are compact, powerful, high performing and provide installers with professional welding which is particularly suitable for hydraulic, air conditioning, refrigeration and soft brazing work. **Product safety is guaranteed by 4 dual-protection flashback arrestor valves positioned on the torch body and inside the reducer and the tap.**

Numerous accessories, filler metals and spare parts are available making work even easier.

KIT:

TURBO SET 200

TURBO SET 110

TURBO SET 90

TURBO SET 30

CARTRIDGES AND CYLINDERS

SPARE PARTS

FILLER METALS



* Weight and dimensions refer to models 200-110-90.
The Turbo set 30 model is even smaller in size and weight



3100°C

TURBO SET 200



TURBO SET 200, SMALL AND POWERFUL

The most professional amongst small autogenous welding systems with non-refillable cylinders. Compact and in a stylish metal trolley, for powerful welding. This Turbo Set allows great flexibility in welding, brazing and heating with a choice of 5 different tips. It is the best choice for installers in thermo-hydraulics, conditioning and refrigeration. Product safety is guaranteed by 4 dual-protection flashback arrestor valves positioned on reducers and inside the torch.

ATTENTION TO DETAIL

A very compact kit: 27 cm high, an inclination of 30° to avoid overturning with fixing brackets for disposable cylinders. The presence of pressure gauges on reducers enables continued monitoring of oxygen cylinder pressure and optimisation of gas cylinder reducer regulation.

EQUIPPED WITH:

- 1 L 110 bar OXYGEN cylinder
- PRO//Max 400g CGA600 cylinder
- MIGNON oxygen and gas reducers with pressure gauge and dual-protection flashback arrestor valves
- Handle with adjusting taps and no-return integrated oxygen and gas
- 160 L lance and tip (tip in two components)
- 2 m hoses with connections
- Set of 4 tips 63-100-250-315 L (in two components)
- Protective goggles
- 2 multi-purpose wrenches
- Igniter
- Filler metal with de-oxidant

GAS CONSUMPTION
(normal regulation
and 160 L tip)

117 g/h

**ENDURANCE OF THE O₂
CYLINDER 0.30 h**

**ENDURANCE OF THE PRO//MAX
CYLINDER 3.40 h**

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
111010	TURBO SET 200 M12X1	6.40	2	41 x 25 x 37	13.00
111011	TURBO SET 200 M11X1 LH	6.40	2	41 x 25 x 37	13.00

SPARE PARTS FOR TURBO SET 200

CODE	Description	Connection	Weight (kg)	No.Pcs.
220650	Pressure Reducer Mignon O ₂ with h.p. gauge	M12X1	0.52	1
220651	Pressure Reducer Mignon O ₂ with h.p. gauge	M11X1 LH	0.52	1
223855	Pressure Reducer Mignon gas with l.p. gauge	CGA600	0.48	1
110010	Welding assembly kit complete with pressure reducers	M12X1	1.95	1
110016	Welding assembly kit complete with pressure reducers	M11X1 LH	1.95	1
110011	Welding assembly kit without pressure reducers	-	1.00	1
110601	Lance and tip	M12X1	0.06	1
110802	Malleable lance	M12X1-M8X1	0.06	1
110710.ESP	Set of 4 tips 63 - 100 - 250 - 315 L	M8X1	0.08	1



223855

220650

OPTIONAL MALLEABLE LANCE



CURRENT ACCESSOIRES



3100°C

TURBO SET 110



Supplied with PRO//Max 400g cylinder. The range includes accessories such as igniters, protective goggles, 4-tip single block star for small precision welding (goldsmiths, dental technicians, etc.), multi-purpose wrench and filler metal enabling immediate product use.

PATENTED HANDLE

New concept and design integrating no-return valves with dual protection for oxygen and gas in the body.

EQUIPPED WITH:

- 1 L 110 bar OXYGEN cylinder
- PRO//Max 400g CGA600 cylinder
- MIGNON oxygen and gas reducers, without pressure gauge, with dual-protection flashback arrestor valves
- 2 m hoses with connections
- Handle with adjusting taps and no-return integrated oxygen and gas
- 80 L lance and tip (tip in two components)
- 4-tip single block star 63-100-160-225 L for small precision welding
- Protective goggles
- Multi-purpose wrench
- Igniter
- Filler metal with de-oxidant

GAS CONSUMPTION

(normal regulation
and 80 L tip)

92 g/h

ENDURANCE OF THE O₂
CYLINDER 0.30 h

ENDURANCE OF THE PRO//MAX
CYLINDER 4.30 h

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
131090.MP	TURBO SET 110 M12x1	5.80	2	41 x 25 x 37	11.80
131091.MP	TURBO SET 110 M11X1 LH	5.80	2	41 x 25 x 37	11.80

SPARE PARTS FOR TURBO SET 110

CODE	Description	Connection	Weight (kg)	No.Pcs.
220500	Pressure reducer Mignon o ₂ without gauges	M12X1	0.36	1
220501	Pressure reducer Mignon o ₂ without gauges	M11X1 LH	0.36	1
223515	Pressure reducer Mignon gas without gauges	CGA600	0.45	1
110002	Welding assembly kit complete with pressure reducers	M12X1	1.40	1
110015	Welding assembly kit complete with pressure reducers	M11X1 LH	1.40	1
110005	Welding assembly kit without pressure reducers	-	0.60	1
110600	Lance and tip	M10X1	0.07	1
110730.ESP	Set of 4 tips 63 - 100 - 160 - 225 L	M6X1	0.06	1



223515

220500

CURRENT ACCESSOIRES



3000°C

TURBO SET 90



Compact, powerful, high performing and provides hobbyists with professional welding, particularly suitable for hydraulic, air conditioning, and refrigeration work. Product safety is guaranteed by 4 dual-protection flashback arrestor valves positioned inside the torch body, on the reducer and on the tap. Wide range of standard accessories

ATTENTION TO DETAIL

Very lightweight kit. Its practical handle and cylinder locking device ensure transportability anywhere. These details make it a useful welding kit for refrigerator technicians, goldsmiths and demanding hobbyists.

EQUIPPED WITH:

- 1 L 110 bar OXYGEN cylinder
- MAXY GAS cartridge
- MIGNON oxygen reducer, **without pressure gauge**, and gas tap, with dual-protection flashback arrestor valves
- 2 m hoses with connections
- Handle with adjusting taps and no-return integrated oxygen and gas valves
- 80 L lance and tip (tip in two components)
- 4-tip single block star 63-100-160-225 L for small precision welding
- Protective goggles
- Multi-purpose wrench
- Igniter
- Filler metal with de-oxidant

GAS CONSUMPTION

(normal regulation
and 80 L tip)

92 g/h

ENDURANCE OF THE O₂
CYLINDER 0.30 h

ENDURANCE OF THE MAXY GAS
CARTRIDGE 3.30 h

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
115050	TURBO SET 90 M12X1	5.50	2	41 x 25 x 37	11.20
115051	TURBO SET 90 M11X1 LH	5.50	2	41 x 25 x 37	11.20

SPARE PARTS FOR TURBO SET 90

CODE	Description	Connection	Weight (kg)	No.Pcs.
220500	Pressure reducer Mignon O ₂ without gauges	M12X1	0.36	1
220501	Pressure reducer Mignon O ₂ without gauges	M11X1 LH	0.36	1
201500	Gas tap	7/16	0.12	1
110000	Welding assembly kit complete with pressure reducers	M12X1	1.40	1
110001	Welding assembly kit complete with pressure reducers	M11X1 LH	1.40	1
110005	Welding assembly kit without pressure reducers	-	0.60	1
110600	Lance and tip	M10X1	0.07	1
110730.ESP	Set of 4 tips 63 - 100 - 160 - 225 L	M6X1	0.06	1



201500

220500

CURRENT ACCESSOIRES



2850°C

TURBO SET 30

TURBO SET 30: HIGH PERFORMANCE, SAFE, ECONOMIC

Autogenous brazing unit with non-refillable cylinder and cartridge with 110 bar of oxygen and 330 grams of propane/butane. Guarantees maximum safety in use and allows a wide variety of performance in multiple soft and hard brazing applications.

ALWAYS ON HAND, LIGHTWEIGHT AND EASY TO HANDLE

The ideal tool for demanding hobbyists for small DIY and modelling projects.

ATTENTION TO DETAIL

A very compact kit. Reliable with inclined cylinder holder support to prevent overturning with fastening support blocked with through screws and threaded nut.

EQUIPPED WITH:

- 1 L 110 bar OXYGEN cylinder
- Propan/Butan 330 g cartridge
- MICRO oxygen and gas reducer with no-return valves
- Handle with adjusting taps, 50 L lance and tip
- 1.5 m hoses with connections
- Protective goggles
- Filler metal with de-oxidant



GAS CONSUMPTION

(normal regulation and 50 L tip)

44 g/h

ENDURANCE OF THE O₂
CYLINDER 1.00 h

ENDURANCE OF THE GAS
CARTRIDGE 7.00 h

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
117050	TURBO SET 30 M12x1	3.15	4	37 x 29.50 x 36.5	12.80
117051	TURBO SET 30 M11X1 LH	3.15	4	37 x 29.50 x 36.5	12.80

SPARE PARTS FOR TURBO SET 30

CODE	Description	Connection	Weight (kg)	No.Pcs.
210022	Pressure reducer Micro O ₂ without gauges	M12X1	0.18	1
210023	Pressure reducer Micro O ₂ without gauges	M11X1 LH	0.18	1
201500	Gas tap	7/16	0.12	1
110008	Welding assembly kit complete with pressure reducers	M12X1	0.70	1
110017	Welding assembly kit complete with pressure reducers	M11X1 LH	0.70	1
110009	Welding assembly kit without pressure reducers	-	0.40	1
110602	Lance and tip	M10X1	0.07	1



CURRENT ACCESSOIRES



TURBO SET SPARE PARTS AND ACCESSORIES



COMMON ACCESSORIES

Oxyturbo Turbo Sets are complemented by a range of accessories that allow for greater ease and speed of use: protective goggles, igniter with flint and multi-purpose wrench.

CODE	Description	Weight (kg)	No.Pcs.
100000	Protective goggles	0.07	1
101000	Igniter	0.05	1
102000	Multi-purpose wrench	0.09	1



480300

483580



483200

483150

DISPOSABLE CYLINDERS AND CARTRIDGES

TURBO SET 200 and 110 are fuelled by a 110 bar oxygen cylinder and a PRO//Max cylinder with a high calorific value gas mixture that allows installers to perform much of the work in the thermo-hydraulic and air conditioning sector.

TURBO SET 90 and 30 are fuelled with disposable cylinders and cartridges supplied in kits and which are easily available. The 110 bar oxygen cartridge and Maxy Gas and Propan/Butan cartridges ensure good autonomy.

CODE	Description	Connection	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
480300	OXYGEN CYLINDER 110 Bar 1 L	M12X1	1.30	12	32 x 24 x 34	15.80
480301	OXYGEN CYLINDER 110 Bar 1 L	M11X1 LH	1.30	12	32 x 24 x 34	15.80
483580	PRO//MAX CYLINDER 400 g	CGA600	0.90	12	46 x 15.5 x 28	11.00
483200	MAXY GAS CARTRIDGE 350 g	7/16 VALVE	0.30	12	31 x 24 x 29	3.60
483150	PROPAN/BUTAN CARTRIDGE 330 g	7/16 VALVE	0.50	24	42 x 29 x 28	12.20

SPARE HOSES

Spare hoses for our welding kits can be cut to the desired size. They are constructed with 16-wire mesh and marked according to standard EN1327 with operating pressure, inner hose diameter and the quarter and year of manufacture.

CODE	Description	No.Pcs.
451005	Orange gas hose ø 3.2 X 8.8 EN 1327	1
450005	Blu oxygen hose ø 3.2 X 8.8 EN 1327	1

USE SUGGESTIONS

TURBO SET 200




TURBO SET 110



TURBO SET 90

FILLER METALS



Filler metal is defined as a metal that can be used in addition to the base metal for welding. The right choice of filler metal allows for good welding. Knowing how to weld means choosing a good technique and a suitable metal for the work to be done. For help, see the table below.



**NO
CADMIUM**

CODE	USE		Specifications	Resistance	Tool heat	No.pcs for pack
101500	IRON WELDING	●	BRASS ALLOY WITH DE-OXIDANT	HIGH	720°C	10
101510	BRAZE-WELDING	●	COPPER ALLOY 93% - PHOSPHOROUS 7%	HIGH	660°C	10
101550	UNIVERSAL	●	SILVER ALLOY 45% WITH DE-OXIDANT	HIGH	640°C	5
101595	BRAZING	●	ALUMINIUM ALLOY 86% WITH DE-OXIDANT	LOW	540°C	7
101590	HYDRAULIC REPAIRS	●	TIN ALLOY 50% WITH DE-OXIDANT	LOW	240°C	2

Larger packs with 300 mm long rods are available for the most demanding professionals:

CODE	USE		Specifications	Resistance	Tool heat	Pack weight (kg)
101500.500	IRON WELDING	●	BRASS ALLOY WITH DE-OXIDANT	HIGH	720°C	500
101510.500	BRAZE-WELDING	●	COPPER ALLOY 93% - PHOSPHOROUS 7%	HIGH	660°C	500
101550.100	UNIVERSAL	●	SILVER ALLOY 45% WITH DE-OXIDANT	HIGH	640°C	100
101595.500	BRAZING	●	ALUMINIUM ALLOY 86% WITH DE-OXIDANT	LOW	540°C	500
101590.500	HYDRAULIC REPAIRS	●	TIN ALLOY 50% WITH DE-OXIDANT	LOW	240°C	500

Metas to join	LEAD	ZINC	IRON	COPPER	BRASS	ALUMINIUM
LEAD	● CODE 101590	● CODE 101590	● CODE 101590	● CODE 101590	● CODE 101590	
ZINC	● CODE 101590	● CODE 101590	● CODE 101590	● CODE 101590	● CODE 101590	
IRON	● CODE 101590	● CODE 101590	* ● CODE 101590 ● CODE 101550 ● CODE 101500	* ● CODE 101590 ● CODE 101550	* ● CODE 101590 ● CODE 101550	
COPPER	● CODE 101590	● CODE 101590	* ● CODE 101590 ● CODE 101550	* ● CODE 101590 ● CODE 101550 ● CODE 101510 ● CODE 101500	* ● CODE 101590 ● CODE 101550	
BRASS	● CODE 101590	● CODE 101590	● CODE 101590 ● CODE 101550	* ● CODE 101590 ● CODE 101550 ● CODE 101510 ● CODE 101500	* ● CODE 101590 ● CODE 101550 ● CODE 101500	
ALUMINIUM						● CODE 101595

* Mechanical resistance varies depending on the filler metal used



SMALL WELDERS WITH BIG PERFORMANCE

Sensitive to the needs of installers in the hydraulics, conditioning and DIY fields, Oxyturbo offers several high-performing, flexible and versatile items to enable useful and practical work solutions. A complete line of easy-to-use manual, safe and strictly tested torches allows you to perform:

- **Soft and hard brazing**
- **Tinning**
- **Paint stripping**
- **Scraping**
- **Thawing**
- **Plastic material welding**



Fuelled by 190g universal cartridges or with 7/16 valve cartridges, they come equipped with a range of accessories allowing the user to perform small repairs.

OXYLASER

Easy, fast welding.

Oxyturbo offers a range of practical professional manual or piezo ignition wrenches, with anatomic handgrips. Ideal for DIY, single-handed use and for soft and hard welding up to **1,750°C**. Equipped with a high yield 21 mm diameter OT burner. Suitable for small repairs, DIY projects, plastic bending and welding, paint stripping and wood drying.



Fuelled by BUTAN/PROPAN 98/2 190g cartridges with a safety device.

DVGW APPROVED



OXYLASER



OXYLASER PIEZO



OXYLASER IRON PIEZO



OXYLASER IRON

VERSIONS AVAILABLE:

OXYLASER - OXYLASER PIEZO with plastic cartridge holder

OXYLASER IRON - OXYLASER IRON PIEZO with iron cartridge holder

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
505000	Oxylaser	0.60	10	54 x 40 x 21	6.65
505080	Oxylaser + 4 Cartridges	1.90	6	60.5 x 40.5 x 20.5	11.60
505070	Oxylaser + 5 Cartridges	2.10	6	60.5 x 40.5 x 20.5	12.80
505020	Oxylaser + Flat Burner And Tinning Nozzle	0.78	10	54 x 40 x 21	8.35
505030	Oxylaser + 3 Accessories	0.82	10	54 x 40 x 21	8.75
505100	Oxylaser Piezo	0.66	10	54 x 40 x 21	7.15
525000	Oxylaser Iron	0.68	10	54 x 40 x 21	7.30
525100	Oxylaser Iron Piezo	0.72	10	54 x 40 x 21	7.60

ACCESSORIES NOT INCLUDED



A range of accessories (not included unless specifically indicated and **not to be used on the piezo version**) which can enhance the welders range.

CODE	Description	Weight (kg)	No.Pcs.
570905	Cercoflamme M12x0.75	0.11	1
570702	Tinning nozzle ø 22 mm	0.05	1
570800	Flat flame burner ø 22 mm	0.04	1

OXYFLEX

A small kit with high heating power.

Oxyflex is a movable manual welding kit with high a yield suitable for small, soft and hard welding, heating, thawing, drying, stripping, thermoplastic treatment, tinning, and smelting. Particularly suitable for demanding DIY projects thanks to its exceptional sturdiness. Its components (extension tube and burner) are the same as those of the OXYWELDER range.



Fuelled by BUTAN/PROPAN 98/2 190g cartridges with a safety device.

IMQ APPROVED



OXYFLEX



OXYFLEX IRON

PROVIDED WITH:

- Handgrip with tap
- OT 100 mm extension
- OT Ø 22 mm high heating power burner
- Belt hook
- 2 m flexible hose
- Tap on cartridge holder

AVAILABLE IN FOLLOWING VERSIONS:

OXYFLEX with plastic cartridge holder

OXYFLEX IRON with iron cartridge holder

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
504000	OXYFLEX	0.84	10	54 x 40 x 21	8.95
524000	OXYFLEX IRON	0.85	10	54 x 40 x 21	9.15

ACCESSORIES NOT INCLUDED



Oxyflex can be combined with a range of accessories which are sold separately.

CODE	Description	Weight (kg)	No.Pcs.
583805	Cercoflamme M10x1	0.12	1
570702	Tinning nozzle ø 22 mm	0.05	1
570800	Flat flame burner ø 22 mm	0.04	1

MAXYLASER MINILASER

Welding kit suitable for maintenance and emergency works.

Oxyturbo offers a set of kits that are very useful for DIY, nautical and agriculture: brazing, tinning, descaling, stripping and thousands of other uses. A series of interchangeable brass burners completes the range.



**Fuelled by PROPAN/BUTAN
210g – 330g with 7/16" valve**

CE APPROVED

AVAILABLE IN FOLLOWING VERSIONS:

MAXYLASER KIT

Provided with:

- Fixed tap with 22 mm diameter OT burner
- Flat flame burner
- PROPAN/BUTAN 330 g cartridge
- support spring

MINILASER Ø 22 KIT

Provided with:

- Fixed tap with 22 mm diameter OT burner
- 14 mm diameter OT burner
- 22 diameter flat flame burner
- PROPAN/BUTAN 210 g cartridge
- Support spring
- Multi-purpose spanner

MINILASER Ø 18 KIT

Provided with:

- Fixed tap with 18 mm diameter OT burner
- 14 mm diameter OT burner
- PROPAN/BUTAN 210 g cartridge
- Support spring
- Multi-purpose spanner



CODE	Description	Weight (kg)	No. Pcs.	Pack. Dim. (cm)	Pack. Weight (kg)
573000	MAXYLASER	0.80	10	55.5 x 23.5 x 28	8.20
572500	MINILASER Ø 18	0.70	10	41 x 22 x 21	7.20
572000	MINILASER Ø 22	0.76	10	41 x 22 x 21	7.80
572590	FIXED TAP + OT 22	0.20	50	41 x 36 x 24	10.20
572591	FIXED TAP + OT 18	0.17	50	41 x 36 x 24	8.70
572592	FIXED TAP + OT 14	0.15	50	41 x 36 x 24	7.50



572592



572591



572590

MANUAL TORCHES

High performance and versatile. Offering practical work solutions.

MULTI-PURPOSE TORCH CGA600



Its spiral flame is designed to wrap the circumference of the hose and reach a temperature of 2010°C. The nozzle is made of brass, the body is aluminium and the other components are manufactured in stainless steel to prevent rust. It is equipped with a safety button that locks the torch while keeping the flame on and the fingers free. It allows inclination and overturning from the ignition phase without wasting fuel and at no risk to the user. Fuelled by PRO//Max 400 g or Maxy Gas 350 g by means of a transformation fitting.

CODE	Description	Weight (kg)	No.Pcs.
574101	MULTI-PURPOSE TORCH CGA600	0.70	1
490280	ADAPTER CGA600 - 7/16	0.08	1

EASYLASER KIT



A new accessory offered as an indispensable tool for installers and plumbers who need to do small soft and hard brazing jobs. Its flame wraps completely the part that is to be welded, assuring an optimal performance even in an inclined or upside-down position. The EasyLaser Kit is a small lightweight, ergonomic torch with a piezo ignition and anti-flaring device which starts working after 15 seconds from the ignition.

Fuelled by Maxy Gas 350 g cartridge with 7/16 valve

The kit is provided with:

- 7/16 Microtorch
- Maxy Gas cartridge

Also available with an adaptor for use with PRO//Max CGA600 cylinders.

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
574150	EASYLASER KIT	0.80	10	55.5 x 23.5 x 28	8.20
498257	ADAPTER 7/16 - CGA600	0.08	25	14 x 11 x 11.5	2.10

MICROTORCH



Small, especially lightweight, ergonomic torch with piezo ignition, equipped with a special burner that avoids the "liquid phase" of the upside-down cylinder gas after 15 seconds from ignition. Can be connected directly to **PRO//Max and Maxy Gas** cylinders which can be interchanged with one another due to the use of special fittings. The Microtorch reaches a temperature of approximately **1850°C** for soft and hard brazing works.

CODE	Description	Weight (kg)	No.Pcs.
574102	MICROTORCH CGA600	0.30	1
574103	MICROTORCH 7/16	0.30	1
498257	ADAPTER 7/16 - CGA600	0.08	1
490280	ADAPTER CGA600 - 7/16	0.08	1

HEATING TORCH KIT

A practical work case containing all your needs for
brazing and heating.

OXYPRO



It uses a high heating power torch which avoids the liquid phase from ignition and reaches a temperature of **2010°C** with PRO//Max and **1960°C** with Maxy Gas.

OXYPRO

Equipped with:

- 1 multi-purpose torch with CGA600 connection
- 2 PRO/Max cylinders

CODE	Description	Weight (kg)	No.Pcs.
585320	OXYPRO	2.00	1

OXYPLUS



OXYPLUS

Equipped with:

- 1 multi-purpose torch with CGA600 connection
- 1 CGA600 - 7/16 adapter
- 2 Maxy Gas cartridges

CODE	Description	Weight (kg)	No.Pcs.
585300	OXYPLUS	2.00	1

Components separately available: torches, PRO//Max cylinder, Maxy Gas cartridge.


DISPOSABLE CYLINDERS AND CARTRIDGES

A range of gas cartridges and cylinders to choose from depending on the different connections and uses. Transformation fittings allow the PRO//Max cylinder and the MAXY GAS cartridge to be interchangeable

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
483002	BUTAN/PROPAN 98/2 CARTRIDGE 190g	0.27	36	28 x 37 x 25.5	10.20
483200	MAXY GAS CARTRIDGE 350 g 7/16 VALVE	0.50	12	31 x 24 x 29	3.60
483580	PRO//MAX CYLINDER 400 g CGA600	0.90	12	46 x 15.5 x 28	11.00
483100	PROPAN/BUTAN CARTRIDGE 210 g 7/16 VALVE	0.31	24	28.5 x 22 x 35.5	7.60
483150	PROPAN/BUTAN CARTRIDGE 330 g 7/16 VALVE	0.46	24	42 x 29 x 28	12.20



USE SUGGESTIONS



GAS CONTROL



**Technological gas leakage detector.
An extremely useful tool for your safety.**



This product is designed to test the hermetic sealing of systems using any type of gas. The liquid used in the gas leakage detector has a special formula against corrosion if used on copper, brass and steel.

DVGW approved in accordance with DIN EN 14291

The gas leakage detector reveals any leak forming bubbles or foam.

CODE	Description	Weight (Kg)	No.Pcs.
405000.EX	DISPLAY 12 PCS. 400 g WITH ACC-U-SOL VALVE	0.46	2X12



ACC-U-SOL
VALVE




MONOGAS WELDING

Oxyturbo offers a complete range of gas torches to meet increasingly sophisticated customer needs. Composable, versatile, useful for soft and hard welding and for professional works such as waterproofing, asphaltting and thermoplastic forging.

Through its specialised experience in the monogas welding field, Oxyturbo has also created the Oxywelder kit which allow users to find the ideal coordinated solution for their own work needs.

OXYWELDING

2 ergonomic handgrips, 5 extension pipes, 4 series of burners, a range of accessories, regulators and pipe fittings allow you to create the most complete range of appliances.



HANDGRIPS

IMQ APPROVED

Ergonomic, sturdy, easy-to-handle, available in two models: normal and with gas-saving lever handgrip for professional use. Utilises different extension pipes and burners for various uses. Connection with G 3/8 right extension pipe. Connection to G 3/8 left hose.



CODE	Description	Extension pipe connection	Hose connection	Weight (kg)	No.Pcs.
584600	HANDGRIP	G 3/8	G 3/8 LH	0.32	1
584650	HANDGRIP WITH GAS-SAVING LEVER	G 3/8	G 3/8 LH	0.38	1

A series of extension pipes, each of which can be screwed to burners of various sizes. All have G 3/8 right connections and vary from 100 to 600 mm. Completing the range is the bi-burner extension, consisting of a 600mm extension and a terminal for 2 burners.



CODE	Description	Connection	Length (mm)	Weight (kg)	No.Pcs.
584710	EXTENSION PIPE L= 100 mm	M10X1 - G 3/8	100	0.07	1
584720	EXTENSION PIPE L= 200 mm	M10X1 - G 3/8	200	0.08	1
584740	EXTENSION PIPE L= 400 mm	M10X1 - G 3/8	400	0.13	1
584760	EXTENSION PIPE L= 600 mm	M10X1 - G 3/8	600	0.17	1
584755	EXTENSION PIPE L= 600 mm	G 3/8 - G 3/8	600	0.20	1
584750	BI-BURNER EXTENSION PIPE	M10X1 - G 3/8	600	0.32	1



BURNERS

OT BURNERS in brass with pin point flame, ideal for soft brazing.

CODE	Description	Connection	Diameter (mm)	Weight (kg)	No.Pcs.
583800	OT BURNER	M10X1	14	0.04	1
583801	OT BURNER	M10X1	18	0.06	1
583802	OT BURNER	M10X1	22	0.07	1

TURBO BURNERS, equipped with air adjusting lances and TURBO burners with enveloping flame. Recommended for hard brazing, watertight welding, thermo-plastic forging and works on copper.

CODE	Description	Connection	Diameter (mm)	Weight (kg)	No.Pcs.
584820	TURBO BURNER	G 3/8	21	0.20	1
584821	TURBO BURNER	G 3/8	25	0.24	1
584822	TURBO BURNER	G 3/8	28	0.32	1

FE BURNERS, in iron with high heating power, rear air mixing. Ideal for waterproofing, hardening and thawing works

CODE	Description	Connection	Diameter (mm)	Weight (kg)	No.Pcs.
584850	FE BURNER	M10X1	30	0.08	1
584851	FE BURNER	M10X1	45	0.17	1
584852	FE BURNER	M10X1	60	0.26	1

ASP BURNERS, with high heating power side suction. Ideal for asphaltting, waterproofing, and thawing works.

CODE	Description	Connection	Diameter (mm)	Weight (kg)	No.Pcs.
584862	ASP BURNER	M10X1	60	0.32	1

ACCESSORIES

The range is complemented by a series of useful accessories to facilitate soft welding works, to aid the transport of cylinders and to relieve vertical waterproofing work.



ACCESSORIES FOR OT 22 BURNERS

CODE	Description	Weight (kg)	No.Pcs.
570702	TINNING NOZZLE	0.05	1
570800	FLAT FLAME BURNER	0.04	1
583805	CERCOFLAMME M10X1	0.12	1

LANCE WITH COPPER MALLET

Ideal for welding metals like core plates. Available with spare 165 g copper mallet.



CODE	Description	Weight (kg)	No.Pcs.
584890	LANCE WITH COPPER MALLET	0.33	1
570750	COPPER MALLET 165 g	0.22	1

FITTED HOSES

Oxyturbo provides a series of approved fitted hoses of varying lengths and diameters to meet any end-user needs.



CODE	Description	Weight (kg)	No.Pcs.
444500	FITTED HOSE 1.5m 4X11DVGW-DK10- KEY 25 – G 3/8 LH	0.29	1
444502	FITTED HOSE 1.5m 4X11DVGW-DK10- KEY 27 – G 3/8 LH	0.35	1
441501	FITTED HOSE 2m 3,2X8,8 – G 3/8 LH	0.21	1
441601	FITTED HOSE 5m 4X11 DVGW-DK6 –G 3/8 LH	0.76	1
441602	FITTED HOSE 1.5m 4X11 DVGW-DK6 – G 3/8 LH	0.23	1



CYLINDER HOLDER TROLLEYS - HOOK

An eye-catching, highly-designed trolley made for transporting LPG cylinders, equipped with chain and burner support and furnished with full rubber 125 mm diameter wheels. Suitable for rough terrain and can withstand weights up to 60 kg.

CODE	Description	Weight (kg)	No.Pcs.
580000	CYLINDER HOLDER TROLLEY	2.65	1
584700	SUPPORT HOOK Ø 12 mm	0.80	1

REGULATORS



CODE	Description	Weight (kg)	No.Pcs.
422000	REGULATOR IT - KEY 25	0.20	1
422001	REGULATOR DE - KEY 30	0.30	1
422002	REGULATOR FR - KEY 27	0.26	1
422003	REGULATOR GB - G5/8	0.30	1
422008	REGULATOR SVE - JUMBO	0.50	1
422009	REGULATOR DK - JUMBO	0.50	1

OXYWELDER KIT



The ideal coordinated solution for your work needs. The kits work with LPG cylinders and are supplied with a nut and hose connection.

WELDER KIT

IMQ APPROVED

WELDER

Composed of: Handgrip - 100mm extension pipe - OT burner

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
601050	KIT with burners Ø 14 + 18 + 22mm	0.70	10	34.5 x 14.5 x 23	7.20
601200	KIT with burner Ø 18mm	0.50	10	34.5 x 14.5 x 23	5.20
601300	KIT with burner Ø 22mm	0.45	10	34.5 x 14.5 x 23	4.70

WELDER COMPLET

Composed of: Handgrip - 100mm extension pipe - 22mm diameter OT burner - 1.5 mm fitted hose

CODE	Description	Connection	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
611300	WELDER COMPLET with 1.5 m 4 x 11 fitted hose	3/8 LH - KEY 25	0.75	10	41 x 36 x 24	8.00
611320	WELDER COMPLET with 1.5 m 4 x 11 fitted hose	3/8 LH - KEY 27	0.80	10	41 x 36 x 24	8.50
611380	WELDER COMPLET with 1.5 m 4 x 11 fitted hose + tap M16x1.5	3/8 LH - KEY 27	0.85	15	41 x 36 x 24	13.00
611310	WELDER COMPLET with 2.0 m 3.2 x 8.8 fitted hose	3/8 LH - 3/8 LH	0.70	10	41 x 36 x 24	7.50

WELDER 100

Composed of: Handgrip - 100mm extension pipe - FE burner

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
603100	KIT with burner Ø 45mm	0.60	20	46 x 29.5 x 26	12.20
603200	KIT with burner Ø 60mm	0.70	20	46 x 29.5 x 26	14.20

WELDER 200

Composed of: Handgrip with gas saving lever - 200mm extension pipe - 45mm diameter FE burner

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
655600	KIT with burner Ø 45mm	0.70	20	46 x 29.5 x 26	14.20



WELDER 400

Composed of: Handgrip - 400mm extension pipe - 60mm diameter burner




CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
606200	Handgrip + FE burner	0.85	10	73.5 x 30.5 x 22.7	8.70
656700	Handgrip with gas-saving lever + ASP burner	0.90	10	73.5 x 30.5 x 22.7	9.20



WELDER 600

Composed of: Handgrip -600mm extension pipe - 60mm diameter burner



CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
609200	Handgrip + FE burner	0.95	6	73.5 x 30.5 x 23	5.90
659700	Handgrip with gas-saving lever + ASP burner	1.00	6	73.5 x 30.5 x 23	6.20



COPPER AND COPPER COMPLETE

Composed of: Handgrip - lance with copper mallet - support hook



CODE	Description	Connection	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
600000	Copper	3/8 LH	0.70	10	34.5 x 14.5 x 23	7.10
610000	Copper complet with 1.5 m 4x11 fitted hose	3/8 LH - KEY 25	0.97	10	41 x 36 x 24	9.90
610020	Copper complet with 1.5 m 4x11 fitted hose	3/8 LH - KEY 27	1.15	10	41 x 36 x 24	11.70
610010	Copper complet with 2.0 m 3.2X8.8 Fitted hose	3/8 LH - 3/8 LH	1.15	10	41 x 36 x 24	11.70

GARDEN OXYTURBO

A line of products with a 'Green Soul'

Sensitive to new market demands, Oxyturbo is proud to present a range of outdoor maintenance products for homes, gardens, paths and walkways. They avoid the use of polluting chemicals that are harmful to our health, as per European Directive 2009/128/EC implemented by Legislative Decree 14/08/2012 n°150 on the environment. This sets rules for the use and reduction of pesticides, reducing the risks and impacts on human health and promoting the use of non-chemical alternatives.





GARDEN RANGE

A generation of devices with built-in piezo ignition. Practical, powerful, safe, ecological, with no risk to people or animals. The speed of their commissioning and piezo ignition makes them immediately usable as needed.

IN THE REFILLABLE CYLINDER VERSION (Biomegaflamme, Bioproflamme, Biosuperproflamme, Superbioflamme, Laserbrenner).

FOR DISPOSABLE CARTRIDGES (Bioflamme)




These can be used all-year long.

SPRING: weed-burning for courtyards, tree-lined paths, paved terraces, sidewalk walls and edges.

SUMMER: barbecue ignition, destruction of insect nests in the soil: Bioflamme allows you to remove wasp nests in the soil or in old walls.

AUTUMN: ignition of fires with branches from pruning and plant residues.

WINTER: pipe thawing (except PVC pipes), defrosting of outside stairs, terraces, etc. to avoid slips and falls.




BIOFLAMME

**A new generation of burners with built-in piezo ignition.
Practical, powerful, safe, ecological, with no risk to people
or animals.**



**Fuelled by PROPAN/BUTAN 330g
WITH 7/16" VALVE**



FEATURES

- ▶ Fuelled by PROPAN/BUTAN 330 g cartridges with 7/16" valve code 483150
- ▶ Practical piezo ignition
- ▶ Gas flow adjustment in the handgrip

USE

Eliminates weeds from terraced paths and walkways, incinerates insect nests, thaws piping, quickly ignites fireplaces and barbecues.

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
571860	With pin-point burner with 1 gas cartridge in colour box	1.48	5	80.5 x 38 x 22	7.60

SUPERBIOFLAMME

High heating power torch to be used with refillable LPG cylinders.
Complete with 600 mm lance and 60 mm flat burner with large flame surface.



HANDGRIP WITH GAS-SAVING LEVER

PIEZO IGNITION



SUPERBIOFLAMME ECO

Provided with:

- Gas-saving lever handgrip with lance and burner
- Support hook

Also available in various versions:

SUPERBIOFLAMME 5000 ECO

Provided with:

- Gas-saving lever handgrip with lance and burner
- Support hook
- 5 m 4x11 DK6 fitted hose



SUPERBIOFLAMME 5000 TK ECO

Provided with:

- Gas-saving lever handgrip with lance and burner
- Support hook
- 5 m 4x11 DK6 fitted hose
- Cylinder holder trolley
- 2.5 bar/6-8 kg* regulator




*Can be supplied with regulators with all country fittings

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
581950	SUPERBIOFLAMME ECO	1.30	6	73.5 X 30.5 X 23	8.00
581970	SUPERBIOFLAMME 5000 ECO	1.85	6	73.5 X 30.5 X 23	11.30
581980	SUPERBIOFLAMME 5000 TK ECO KEY 25	4.65	1	79 x 30.5 x 16.5	4.65
581981	SUPERBIOFLAMME 5000 TK ECO KEY 30	4.75	1	79 x 30.5 x 16.5	4.75
581982	SUPERBIOFLAMME 5000 TK ECO KEY 27	4.70	1	79 x 30.5 x 16.5	4.70
581983	SUPERBIOFLAMME 5000 TK ECO G5/8	4.75	1	79 x 30.5 x 16.5	4.75
581984	SUPERBIOFLAMME 5000 TK ECO JUMBO DK	5.30	1	79 x 30.5 x 16.5	5.30
581985	SUPERBIOFLAMME 5000 TK ECO JUMBO SE	5.30	1	79 x 30.5 x 16.5	5.30

BIOMEGAFLAMME

An environmentally friendly product and an ideal tool for weeding walkways, floors with self-locking devices, lawn edges and generalised interventions.



The Biomegaflamme does not release toxic residues into the environment and can be used in any season. Works with LPG or propane. Equipped with piezo ignition for easy use and limits unnecessary gas consumption.

Provided with:

- Gas-saving lever handgrip
- 600 mm extension pipe with Mega triangular flat flame burner
- Support hook
- 5 m 4x11 DK6 fitted hose

Biomegaflamme can on request be supplied with cylinder holder trolley and equipped with 2.5 bar 6/8 kg pressure regulator with all country fittings.




CODE	Description	Weight (kg)	No. Pcs.	Pack. Dim. (cm)	Pack. Weight (kg)
582950	BIOMEGAFLAMME with piezo ignition and gas-saving lever in colour box	2.40	5	80.5 x 38 x 22	12.20

LASERBRENNER

HIGH CALORIFIC
POWER

Professional kits for waterproofing, asphaltting, pipe thawing, pest control and weed burning.



LASERBRENNER 60

Provided with:

Gas-saving lever handgrip - 600 mm extension pipe - ASP 60 mm diameter burner - Support hook - 5 m 4x11 DVGW-DK6 fitted hose

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
669710	LASERBRENNER 60	1.60	6	73.5 x 30.5 x 23	9.80

LASERBRENNER B45

Provided with:

Gas-saving lever handgrip - 600 mm extension pipe - Terminal for 2 burners - 2 FE 45 mm diameter burners - Support hook - 2 spanners - 5 m 4x11 DVGW-DK6 fitted hose

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
668610	LASERBRENNER B45	2.18	6	73.5 x 30.5 x 23	13.30

LASERBRENNER 60 TK


Provided with:

Laserbrenner 60 - Cylinder holder trolley - 2.5 bar 6/8 kg regulator

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
689700	LASERBRENNER 60 TK KEY 25	4.60	1	79 x 30.5 x 16.5	4.60
689701	LASERBRENNER 60 TK KEY 30	4.70	1	79 x 30.5 x 16.5	4.70
689702	LASERBRENNER 60 TK KEY 27	4.70	1	79 x 30.5 x 16.5	4.70
689703	LASERBRENNER 60 TK G5/8	4.70	1	79 x 30.5 x 16.5	4.70
689704	LASERBRENNER 60 TK JUMBO DK	4.90	1	79 x 30.5 x 16.5	4.90
689705	LASERBRENNER 60 TK JUMBO SE	4.40	1	79 x 30.5 x 16.5	4.90

BIOPROFLAMME

Environmentally friendly product equipped with 3 high heating power burners and a useful working width of approximately 70 cm.



Allows for operation on different types of ground and guarantees absolutely no harmful residues. Suitable for use on tree-lined paths, paved terraces, pipe thawing (not including PVC pipes), and the defrosting of stairs and outside terraces.

Provided with:

- Gas-saving lever handgrip
- 600 mm extension pipe
- Terminal for 3 burners
- 3 FE 45 diameter burners
- Support hook
- 5 m 4x11 DK6 fitted hose


Bioproflamme can on request be supplied with cylinder holder trolley and equipped with 2.5 bar 6/8 kg pressure regulator with all country fittings.



CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
583950	BIOPROFLAMME with 3 burners and gas-saving lever in colour box	2.50	5	80.5 x 38 x 22	12.70

BIOSUPER PROFLAMME

A 4-burner high heating power torch with a useful working width of approximately 90 cm.



Professional kit for intensive weed burning composed of 4 high heating power burners with a useful working width of approximately 90 cm. Ready to use. Runs with LPG or propane. Made to eradicate weeds ecologically in a few days without the use of expensive toxic chemicals. Suitable for weeding large surfaces and other uses requiring the use of a flame. For example; eliminating slippery ice on paths or walkways.

Provided with:

- Gas-saving lever handgrip
- 600 mm extension pipe
- Terminal for 4 burners
- 4 FE 45 diameter burners
- Support hook
- 5 m 4x11 DK6 fitted hose

Biosuperproflamme can on request be supplied with cylinder holder trolley and equipped with 2.5 bar 6/8 kg pressure regulator with all country fittings.




CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
583955	BIOSUPERPROFLAMME with 4 burners and gas-saving lever in colour box	2.70	5	80.5 x 38 x 22	13.70

CYLINDER HOLDER TROLLEYS

Two different models to meet different uses and needs.
They are made to ensure increased space economy and are
in painted metal tube design.

BIG TROLLEY



A practical cylinder holder trolley shaped in a mono-tube. Equipped with 2 sturdy pneumatic rubber wheels with a diameter of 290 mm which allows for use on any type of ground. Equipped with a hook and chain for the cylinder or other container. It can withstand a weight up to maximum 90 kg.

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
580002	Cylinder holder trolley	4.70	1	100 x 19 x 32.5	4.70



TROLLEY



An eye-catching, designed trolley made for the transporting LPG cylinders; equipped with chain and burner support and comes with full rubber 125 mm diameter wheels. Suitable for rough terrain and can withstand weights up to 60 kg.

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
580000	Cylinder holder trolley	2.65	1	79 x 30.5 x 16.5	2.65



SPARE PARTS AND ACCESSORIES

The range is complemented by a series of spare parts and accessories for improved end user service.



HANDGRIPS

Ergonomic, sturdy, easy-to-handle and available in two models: normal and with a gas-saving lever handgrip for professional use. Utilises different extension pipes and burners for various uses. Connection with G 3/8 right extension pipe. Connection to G 3/8 left hose

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
584600	HANDGRIP	0.30	10	34 x 14 x 22.5	3.10
584650	HANDGRIP WITH GAS-SAVING LEVER	0.40	10	34 x 14 x 22.5	4.10
584651	HANDGRIP WITH GAS-SAVING LEVER FOR BIOMEGAFLAMME	0.40	10	34 x 14 x 22.5	4.10



BURNER

CODE	Description	Connection	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
584851	Ø 45 mm FE BURNER M10X1	M10X1	0.17	30	41 X 36 X 24	5.30



SUPPORT HOOK

CODE	Description	Weight (kg)	No.Pcs.
584700	STANDARD SUPPORT HOOK	0.10	1
584702	SUPPORT HOOK FOR BIOMEGAFLAMME	0.65	1



FITTED HOSE

CODE	Description	Weight (kg)	No.Pcs.
441601	5 M 4X11 DVGW- DK6 FITTED HOSE G3/8 LH - G3/8 LH	0.76	1



2,5 BAR 6/8 KG REGULATOR

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
422000	IT - KEY 25	0.20	70	40 x 28 x 15	14.20
422001	DE - KEY 30	0.30	70	40 x 28 x 15	21.20
422002	FR - KEY 27	0.30	70	40 x 28 x 15	21.20
422003	GB - G5/8	0.30	70	40 x 28 x 15	21.20
422008	DK - JUMBO	0.50	40	40 x 40 x 24	20.20
422009	SE - JUMBO	0.50	40	40 x 40 x 24	20.20



CARTRIDGE WITH 7/16 VALVE

65 mm diameter cartridges with valve that can be directly connected to equipment and can be replaced at any time even if not completely empty. Contents:

60/40 butane propane mixture (per 210 g)

70/30 butane propane mixture (per 330 g)

CODE	Description	Weight (kg)	No.Pcs.	Pack.Dim. (cm)	Pack.Weight (kg)
483100	PROPAN/BUTAN cartridge 210 g	0.31	24	28.5 x 22 x 35.5	7.60
483150	PROPAN/BUTAN cartridge 330 g	0.45	24	42 x 29 x 28	12.20



OXYTURBO SpA
Via Serio, 15 - 25015 Desenzano del Garda (BS) - Italy
Tel. +39 030-9911855 Fax +39 030-9911271

info@oxyturbo.it www.oxyturbo.it