

Cutting-off wheel **EDGE SPECIAL**



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■■■
Aggression	■■■■■■■□
Service life	■■■■■■■■■

Product benefit

High-performance cutting-off wheel with self-sharpening abrasive grain - Great cutting performance combined with a long service life - Wide range of applications - Packaged in units of 25 in the Kronenflex® Box to preserve maximum performance and protect against moisture

Materials

Stainless steel	●
Steel	●
Aluminium	●

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Stainless steel processing industry
- ▶ Railing construction
- ▶ Metal construction
- ▶ Pipeline construction
- ▶ Locksmith's shop
- ▶ Oil and gas industry

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1,2 x 22,23		80 m/s	13300 rpm	25	355380
125 x 1,2 x 22,23		80 m/s	12250 rpm	25	355379

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

