

Cutting-off wheel

A 24 TZ SPECIAL



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■■□□
Service life	■■■■■□

Product benefit

Optimized combination for use on stainless steel - Excellent performance

Materials

Stainless steel	●
Steel	●
Castings	●

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	136554
125 x 2,5 x 22,23		80 m/s	12250 rpm	25	136555
180 x 3 x 22,23		80 m/s	8500 rpm	25	136558
230 x 3 x 22,23		80 m/s	6650 rpm	25	136559

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

